

Data Sheet



Passive telecoil T 34 AA 01


9012 - 2004205
MT3249.D (01/07)

Description


Inductive pick-up coil for use in hearing instruments.

Features

- Highly durable coating
- Small size
- High sensitivity



Dimensions



Mechanical data

Dimensions	in mm	in inch
Dimension A max.	2	0.079
Dimension B max.	6.35	0.25

Electrical data

Measuring conditions: Temperature = 23°C (73.4F)

Parameters	Min	Typ	Max	Unit	Comments
DC resistance	3078	3420	3762	Ohm	
Inductance @ 1 kHz	371	437	503	mH	
O.C. 1 kHz Sensitivity	-56.8	-55.3	-53.8	dBV/A/m	
10 kOhm load 1 kHz Sensitivity	-59.6	-58.1	-56.6	dBV/A/m	
Resonance frequency	75			kHz	
Winding sense	North positive				

Lead wires

Start lead description: Green, 51 mm, #34 AWG (Ø 0.160 mm), solid Cu with PU coating, 0.7 mm silverplated

Finish lead description: Red, 51 mm, #34 AWG (Ø 0.160 mm), solid Cu with PU coating, 0.7 mm silverplated

Lead wire length measured from edge flange.

Sonion reserves the right to make changes at any time to improve reliability, function or design, in order to provide the best product possible.